Product datasheet

LEDriving SL W5W RED

Ideal replacement for any vehicle

Suitable for various vehicle exterior applications
Available in Red

Replaces conventional W5W lamps
Easy upgrade to LED technology with plug & play solutions

Reliable OSRAM quality stands for less lamp replacements
4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W5W

LEDriving SL W5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2021, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Order reference	2825DRP
Product type (off-road vs. on-road)	Off-road ≙ W5W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications


Electrical data

Power input	0.8 W
Nominal voltage	12.0 V
Test voltage	13.5 V
Power input tolerance	±10 %

Photometrical data

Luminous flux	15 lm
Luminous flux tolerance	±25 %
Light color LED	Red

Dimensions & weight



Diameter	10.0 mm
Product weight	1.94 g

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Additional product data

Base (standard designation)	W2.1x9.5d

© 2021, OSRAM GmbH. All rights reserved.

Product datasheet

Capabilities

Technology	LED [1)]

[1)] Light-emitting diode lamp

Country specific categorizations

Order reference	2825DRP

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172150316	LEDriving SL ≙ W5W	Blister 2	135 mm x 95 mm x 13 mm	0.17 dm^3	15.00 g
4062172150323	LEDriving SL ≙ W5W	Shipping carton box 10	71 mm x 104 mm x 146 mm	1.08 dm^3	109.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	Brochures LEDriving Retrofits - Exchange overview (EN)
	Brochures 618438_LEDriving RETROFIT application overview (EN)
	360 Degree Image LEDriving SL W5W 2825DWP-02B 2825DRP-02B 2827DYP-02B

Safety advice
Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice
These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice
For more detailed application information and graphics please see product datasheet.

© 2021, OSRAM GmbH. All rights reserved.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM

© 2021, OSRAM GmbH. All rights reserved.